
PS80

fa future automation

PULL & SWIVEL MANUAL WALL MOUNT







SPECIFICATION	MEASUREMENTS
Maximum Screen Size	65" - 110"
Maximum Weight Capacity	120Kg (265lb)
Maximum Extension From Wall	569mm (22.4")
Depth From Wall	84mm (3.3")
Packaging Dimensions	970 x 380 x 200mm (38.1 x 14.9 x 7.8")
Shipping Weight	20Kg (44lb)
Maximum Rotation	Screen Dependant - 45° for 65" - 40° for 75" - 34° for 85" - 28° for 100"
Movement Type	Manual
Mounting Patterns Supported	VESA 800, 700, 600, 500, 400, 300, 200 W x 700, 600, 500, 400, 300, 200 H
Product Options / Features	Specific B&O and Loewe mounts / adapters, Custom RAL paint finishes, WB80
Package Contents	Mechanism
Marine Suitable	No



GENERAL DIMENSIONS





TECHNICAL SHEET
ISSUE 004
SHEET 3


WWW.FUTUREAUTOMATION.NET

PS80

PULL & SWIVEL MANUAL WALL MOUNT



WALL PLATE DIMENSIONS





fa future automation

RECESS MOUNTING

When recess mounting a screen on the PS80 the gap around the edge can be as little as 5mm [0.2]. Ventilation would have to be provided by opening the top and maybe the bottom of the recess.

A larger gap of 50mm [2.0"] around the screen would enable extra ventilation and enough space for finger access to manoeuvre the screen if required.





SHEET 5

PS80


PULL & SWIVEL MANUAL WALL MOUNT




MOUNTING DETAILS

The whole area of the wall plate needs to be well supported. Ideally solid plaster over brickwork.

If mounting to a stud work wall its important to have 2 vertical studs behind on both sides of the wall plate. See details A & B.








SWIVEL ANGLES

The width of the screen will determine the possible swivel angle.

75" screens may swivel up to 40 degrees where a 85" screen may swivel up to 34 degrees and 100" up to 28 degrees.



WWW.FUTUREAUTOMATION.NET

SHEET 7